

DTIC FILE COPY

USAARL Report No. 89-16

①



AD-A212 673

# Visual Acuity with AN/PVS-5A Night Vision Goggles and Simulated Flashblindness Protective Lenses Under Varying Levels of Brightness and Contrast

By

Richard R. Levine

and

Clarence E. Rash

Sensory Research Division

July 1989



Approved for public release; distribution unlimited.

89 9 20 019

United States Army Aeromedical Research Laboratory  
Fort Rucker, Alabama 36362-5292

## Notice

### Qualified requesters

Qualified requesters may obtain copies from the Defense Technical Information Center (DTIC), Cameron Station, Alexandria, Virginia 22314. Orders will be expedited if placed through the librarian or other person designated to request documents from DTIC.

### Change of address

Organizations receiving reports from the U.S. Army Aeromedical Research Laboratory on automatic mailing lists should confirm correct address when corresponding about laboratory reports.

### Disposition

Destroy this report when it is no longer needed. Do not return to the originator.


### Disclaimer


The views, opinions, and/or findings contained in this report are those of the authors and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other official documentation. Citation of trade names in this report does not constitute an official Department of the Army endorsement or approval of the use of such commercial items.

### Human use


Human subjects participated in these studies after giving their free and informed voluntary consent. Investigators adhered to AR 70-25 and USAMRDC Reg 70-25 on Use of Volunteers in Research.

Reviewed:

  
BRUCE C. LEIBRECHT, Ph.D.  
LTC, MS  
Director, Sensory Research  
Division

  
J.D. LaMOTHE, Ph.D.  
COL, MS  
Chairman, Scientific  
Review Committee

Released for publication:

  
DAVID H. KARNEY  
Colonel, MC  
Commanding

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
1a. REPORT SECURITY CLASSIFICATION <b>Unclassified</b>			1b. RESTRICTIVE MARKINGS		
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Approved for public release, distribution unlimited		
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE			5. MONITORING ORGANIZATION REPORT NUMBER(S)		
4. PERFORMING ORGANIZATION REPORT NUMBER(S) USAARL Report No. 89-16			6a. NAME OF PERFORMING ORGANIZATION U.S. Army Aeromedical Research Laboratory		
6b. OFFICE SYMBOL (If applicable) SGRD-UAS-VS			7a. NAME OF MONITORING ORGANIZATION U.S. Army Medical Research and Development Command		
6c. ADDRESS (City, State, and ZIP Code)  Fort Rucker, AL 36362-5292			7b. ADDRESS (City, State, and ZIP Code)  Fort Detrick Frederick, MD 21701-5012		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION		8b. OFFICE SYMBOL (If applicable)		9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER	
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO. 62787A		PROJECT NO. 3E162787A879	
		TASK NO. BG		WORK UNIT ACCESSION NO. 164	
11. TITLE (Include Security Classification) Visual Acuity with AN/PVS-5A Night Vision Goggles and Simulated Flashblindness Protective Lenses Under Varying Levels of Brightness and Contrast					
12. PERSONAL AUTHOR(S) Levine, Richard R. and Rash, Clarence E.					
13a. TYPE OF REPORT		13b. TIME COVERED FROM _____ TO _____		14. DATE OF REPORT (Year, Month, Day) 1989 July	
				15. PAGE COUNT 18	
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)		
FIELD	GROUP	SUB-GROUP			
20	06				
23	02		PLZT, nuclear flashblindness protection, aircrew eye protection, visual acuity effects		
19. ABSTRACT (Continue on reverse if necessary and identify by block number) Flashblindness protection from tactical nuclear weapons is an issue of current concern in Army aviation. As a countermeasure, the Army is considering incorporating PLZT goggles/material into the overall design of the Aircrew Integrated Helmet System currently under development. Because present generation flashblindness materials permit about 20 percent light transmission in the open state (about the same as the aviator's sunglasses), flying with PLZT under normal daylight conditions is not expected to impact aviator visual performance adversely. For night missions, PLZT would be used in conjunction with image intensification systems (e.g., night vision goggles [NVGs]). Placing PLZT between the NVG and the eyes would leave the sensitivity of the goggle to environmental lighting unaffected; however, the light available to the eyes from the NVG would be reduced by 80 percent. Because reduction of light from the NVG could further degrade acuity (at best, 20/50-20/60 with NVGs), a					
Continued					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input checked="" type="checkbox"/> UNCLASSIFIED/INLIMITED <input type="checkbox"/> SAME AS PPT. <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION Unclassified		
22a. NAME OF RESPONSIBLE INDIVIDUAL Chief, Scientific Information Center			22b. TELEPHONE (Include Area Code) (205) 255-6907		22c. OFFICE SYMBOL SGRD-UAX-SI

19. Abstract (Continued)

study was performed to determine the effects on visual acuity following an 80 percent reduction in goggle luminous output (e.g., from wearing PLZT in its open state). The results of the study demonstrate that visual acuity with NVGs varies as a function of both ambient illumination and target contrast. However, there were no significant differences in acuity attributable to an 80 percent reduction in NVG output. While these results are encouraging, additional operational testing is required before deciding to incorporate PLZT or any other flashblindness protective material into the aviator's HGU-56/P.

### Acknowledgments

Appreciation is expressed to SPC Vincent Reynoso and SGTs Jim Bohling and Kim Ray for providing expert technical assistance in the collection of data. We also thank SSG John S. Martin for his programming assistance and Dr. Isaac Behar for his professional advice and consultative support. Finally, we thank the participants of the study who sat patiently through the hours of testing while maintaining their vigilance throughout.

Accession For	
NTIS CRA&I	X
DTIC TAB	
Unannounced	
Justification	
Special	
In Reply	
Distribution/Notes	
Author/Editor	
Dist	Special
A-1	



=====

This page intentionally left blank.

=====

## Table of contents

List of figures.....	2
Introduction.....	3
Methods.....	4
Subjects.....	4
Apparatus.....	4
Viewing conditions.....	5
Background CRT luminance.....	5
Target/background contrast level.....	5
Procedures.....	5
Study design.....	8
Results.....	9
Discussion.....	11
Recommendations.....	13
References.....	14
Appendixes	
A--DCD request memorandum.....	15
B--Mean visual acuity with AN/PVS-5A night vision goggles with and without simulated flashblind- ness protective lenses under varying levels of brightness and contrast.....	17
C--Manufacturers' list.....	18

### List of figures

1. Subject viewing the monitor through the mounted AN/PVS-5A night vision goggles.....	5
2. Filter rings unmounted (top) and mounted (bottom) onto the AN/PVS-5A oculars.....	6
3. Examples of Snellen Es at contrasts of 90 percent (top), 30 percent (middle), and 3 percent (bottom).....	7
4. Mean acuities at high, moderate, and low levels of contrast under simulated <u>twilight</u> lighting conditions.....	9
5. Mean acuities at high, moderate, and low levels of contrast under simulated <u>moonlight</u> lighting conditions.....	10
6. Mean acuities at high, moderate, and low levels of contrast under simulated <u>starlight</u> lighting conditions.....	10



## Introduction

Flashblindness protection from tactical nuclear weapons is an issue of current concern in Army aviation. The U.S. Air Force, as a means of protection, provides its crewmembers with PLZT goggles (Richey, Bower, and Allen, 1980). PLZT is an electro-optical ceramic material made from lead (P), lanthium (L), zirconium (Z), and titanate (T). When placed between a pair of crossed polarizers and provided with a low voltage source, this material can rotate the linearly polarized light transmitted from the first polarizer and pass it through the second -- thus enabling the pilot to see out. However, should the goggles' photosensors detect a sudden change in light intensity (e.g., from a nuclear flash), the voltage to the lenses is reduced/removed, and within 150 microseconds the system becomes nearly opaque (optical density > 4.0 [Lindsey, 1988]). This "closed" condition protects the aviator during the peak brightness levels associated with the blast-induced flash. Recovery of the material occurs in conjunction with the dissipation of the light source or with the wearer's head (and sensor) facing in a direction away from the source of bright light.

The Army is considering incorporating PLZT goggles/material into the overall design of the Aircrew Integrated Helmet System (HGU-56/P) currently under development. Tactical doctrine would require rotary-wing pilots to don flashblindness protection in areas of possible or expected tactical (i.e., relatively low-yield) nuclear attack. Because current generation flashblindness goggles permit about 20 percent light transmission in their open state (about the same as the current aviator's sunglasses), flying with PLZT under daylight conditions, in the absence of nuclear blast, is not expected to impact aviator visual performance adversely. However, significant decrements in visual performance have been reported during night flights with PLZT (McLean and Rash, 1985) and the ability to pilot rotary-wing aircraft with the material in its closed state, even for short periods, is as yet unknown.

For night missions, PLZT would be used in conjunction with image intensification ( $I^2$ ) systems. While enhancing visual input under low-light conditions,  $I^2$  systems (e.g., AN/PVS-5 night vision goggles [NVGs]) inherently compromise visual function. NVGs, for example, provide "best" Snellen acuities of only 20/50-20/60. In addition, they restrict field-of-view to approximately 40 degrees, eliminate color cues by presenting a monochromatic (green) image, and degrade depth discrimination at ranges beyond 500 feet (Wiley et al., 1976).

Placing PLZT between an I<sup>2</sup> system such as the NVGs and the eye will leave the sensitivity of the goggles to environmental lighting unaffected. In addition, because PLZT's spectral density is relatively flat over the visible spectrum (Richey, Bower, and Allen, 1980), wearing PLZT (in its open state) should not degrade prevailing color vision. (PLZT's effects on field-of-view and depth-of-field will depend on its physical compatibility with the NVGs.) However, PLZT will reduce the light available from the NVGs to the eye, and these reductions in the already low photopic or mesopic levels of light characteristic of normal NVG output could affect visual acuity adversely.

The Directorate of Combat Developments (DCD), U.S. Army Aviation Center, Fort Rucker, Alabama, requested that the U.S. Army Aeromedical Research Laboratory (USAARL), Fort Rucker, Alabama, evaluate the effects of tandem NVG-PLZT wear on visual function (Appendix A). Additional dialogue with DCD representatives determined that their immediate data needs centered around possible additional visual acuity losses using NVGs with PLZT in its open state. In response to DCD's request, an experiment was performed to determine the effects on visual acuity using NVGs with and without an 80 percent loss of luminous transmission (characteristic of PLZT in its open state) between the NVGs and the eye.

### Methods

Subjects: Eight volunteers, seven military and one civilian ranging in age from 22-37, participated in the study. All but one participant had 20/20 or better Snellen acuity without correction; one myopic subject was corrected to 20/20 with contact lenses. All subjects were familiar with the experimental procedures and had prior experience in acuity testing with NVGs.

Apparatus: Subjects were seated in a darkened room 20 feet from a 12" monochrome CRT monitor. (The spectral distribution of the monitor's P-4 phosphor was compatible with the energy sensitivity of the NVGs.) Subjects viewed the CRT through a single pair of AN/PVS-5A night vision goggles mounted on a table in front of the subject (Figure 1). Both the height and the interpupillary distance of the NVGs were adjusted individually for each subject. PLZT was simulated using a pair of Kodak Wratten No. 96 neutral density filters\*, each having a measured transmittance of approximately 20 percent. The filters were placed in specially constructed rings which attached directly

\* See Appendix C



Figure 1. Subject viewing the monitor through the mounted AN/PVS-5A night vision goggles.

onto the oculars of the NVGs (Figure 2). The filters were attached or removed according to a quasi-random schedule of viewing conditions (see below).

#### Viewing Conditions:

**Background CRT luminance** - Background CRT luminance was measured with a Pritchard 1980-A spot photometer\* and adjusted to simulate ambient light levels associated with twilight (approximately 1/2 hour past sunset), full moon, or starlight (moonless night; RCA Electro-Optics Handbook, 1974). The monitor display served as the only source of light in the room.

**Target/background contrast level** - Three contrast ratios (target and background grey levels) -- 90, 30, and 3 percent -- were selected to represent conditions of high, moderate, and low target/background contrast. (Contrast was defined as  $[\text{target brightness} - \text{background brightness}] / [\text{target brightness} + \text{background brightness}]$ ). The target always appeared darker than its surround (Figure 3).




Figure 2. Filter rings unmounted (top) and mounted (bottom) onto the AN/PVS-5A oculars.




Figure 3. Examples of Snellen Es at contrasts of 90 percent (top), (top), 30 percent (middle), and 3 percent (bottom).

Procedures: Subjects were briefed on their required task and permitted 5-10 minutes to adapt to their darkened surroundings. At the end of this time, they were instructed to focus the tubes of the NVGs while continuously viewing 20/200 and 20/60 targets on the monitor.

Acuity task - A Snellen optotype "E" was displayed on the monitor for 1 second and the subject indicated the orientation of the "E" with an appropriate movement of a hand-held joystick. The orientation of the "E" was varied randomly under computer control in one of the cardinal positions while the size of the "E" was controlled by an operator in an adjacent room. Letter sizes ranged, in terms of Snellen notation, from 20/10 to 20/400. The rate of presentation was about once every 3 seconds.

Threshold determination - Acuity thresholds were determined by incorporating the four-alternative forced-choice procedure into a Wetherill threshold tracking paradigm (Wetherill and Levitt, 1965). Briefly, a single, suprathreshold (e.g., 20/400), "E" was presented randomly in one of the four possible orientations. Progressively smaller targets then were presented until the subject either ceased to respond or responded incorrectly. Increasingly larger-sized letters then were presented until the subject once again responded correctly. At the first correct response, subjects received a second, "confirmatory" trial with the same-sized letter. A second correct response then resulted in the next smaller-sized letter. However, an incorrect response resulted, as before, in the next larger-sized letter. To ensure threshold stability, this up-and-down tracking procedure continued until the subject exhibited a minimum of 12 reversals. After discarding the first two runs to eliminate start-up effects, acuity threshold was calculated as the mean of the values at the next 10 reversal points (i.e., 5 each, maxima and minima). Requiring two correct responses before reducing the target size yields, according to Wetherill and Levitt, the subject's 70 percent response threshold.

Under the more difficult viewing conditions (e.g., starlight and low contrast), subjects often could not correctly identify the orientation of the largest (20/400) letter. On those trials an acuity value of 20/600 was assigned arbitrarily and used in the calculation of the subject's threshold.

Study design: The study was designed as a 3 (brightness: twilight, moonlight, and starlight) x 3 (contrast: high, moderate, and low) x 2 (filters: on and off) randomized factorial with repeated measures (subjects) on all factors. The 18 possible viewing conditions were randomized and presented exhaustively once to each subject. Data collection was accomplished in three sessions for each subject, with each experimental session lasting about 1 hour.

## Results

Figures 4-6 display mean acuities for each contrast level at each level of background illumination. Acuities with NVGs both with and without filters are compared for each light and contrast level condition. The thin vertical bars atop the thicker bars represent the standard deviations of the group means (displayed unidirectionally for clarity of presentation). Acuity is shown both in terms of minimum angle of resolution and its associated Snellen value. (Appendix B presents the same data in a tabular format.)

As can be seen, mean acuities ranged from 20/50 under the most favorable viewing condition (twilight and high contrast) to greater than 20/400 under the poorest. However, from the point of view of the present study, inspection of the data reveals no significant differences in acuity between the "filter" and "no filter" conditions at any combination of brightness and contrast. Thus, over the range of conditions examined, decrements in acuity




Figure 4. Mean acuities at high, moderate, and low levels of contrast under simulated twilight lighting conditions.




Figure 5. Mean acuities at high, moderate, and low levels of contrast under simulated moonlight lighting conditions.




Figure 6. Mean acuities at high, moderate, and low levels of contrast under simulated starlight lighting conditions.



occurred independently of the nearly 80 percent luminous reduction in NVG output which resulted from placing the filter materials over the goggle's oculars.

Discounting the effects of the filters, the data indicate decrements in acuity with decreases either in the level of "ambient" illumination or in the level of target/background contrast. As might be expected, typical "best" AN/PVS-5 acuities (20/50-20/60) were achieved under fairly optimal lighting conditions (i.e., under conditions of relatively high contrast and scene luminance). However, acuity degraded as background brightness decreased from twilight to starlight levels with the most marked decrements (20/125 and worse) exhibited for letters of low (and perhaps the most militarily significant level of) contrast. At the lowest luminance and contrast level (Figure 6), acuity among all subjects degraded beyond measurable levels.

### Discussion

The results of this study confirm visual acuity through NVGs may be impaired under light levels less than ideal for optimal NVG resolution, and, in general, for targets of low contrast. However, under typical NVG viewing conditions, no differential effects on visual acuity were found by looking through a filter which reduced the luminous transmission of the goggles by nearly 80 percent. (Although unsupported by improvements in performance, two subjects reported that, under some conditions, the filters actually enhanced viewing by reducing what they regarded as the distracting "flicker" [goggle "noise"] seen in the undifferentiated visual field [empty room] surrounding the video display.) Thus, by itself, an 80 percent reduction in luminous transmission, characteristic of the "open" state of PLZT, should not further impair visual acuity through the AN/PVS-5 night vision goggles.

Before deciding to adopt PLZT for Army aviation, some additional points should be considered. For example, if PLZT can be represented accurately by neutral density filters, then viewing monochromatic NVG imagery via open PLZT should not further degrade available color cues. However, depending upon its physical compatibility with the goggles, PLZT could force the eye further away from the goggles' exit pupil and reduce the already restricted 40-degree visual field and the resultant perception of depth. Thus, even if visual function is preserved, incompatibility of fit between PLZT and NVGs could impair flying ability by constricting the wearer's visual field to the extent

that his visual input would be analogous to that of viewing a baseball game through a distant knothole. Therefore, we recommend future testing to incorporate prototype or actual headgear in order to avoid subsequent compatibility problems.

Our study also has assumed generally benign environmental and meteorological conditions, i.e., an airframe unaffected by the destructive potential within the actual blast envelope. Unless hardened against the blast's long-range electromagnetic pulse, resultant voltage or current surges could damage or disable vulnerable opto-electronic assemblies in the NVGs leaving viewing through PLZT alone as the only possible visual path. Thus, any consideration of PLZT's potential effects on vision must be divided, conceptually at least, into those associated with the visual interpretation of the NVG image and those related to visual performance in the absence of fully operational NVGs (i.e., with PLZT alone).

Aviator visual performance using PLZT alone will depend on environmental considerations as well as the specific visual task at hand. While not expected to cause problems under bright ambient illumination, PLZT's effects under low-light conditions, in the absence of test data, only can be surmised. Previous work from this Laboratory has shown unacceptable impairments in acuity under low-light conditions in individuals wearing lenses which reduced visual transmittance by 70 percent (Wiley, 1987). Furthermore, preliminary testing by this Laboratory (McLean and Rash, 1985) and by the Air Force (Templin and Thornton, 1978) suggest that viewing through PLZT under low-light conditions may both impair visual performance and degrade tactical flying ability. The degree to which PLZT may impair low-light performance of visual-based tasks, to include those tasks requiring the aviator to look "under" or around nonoperational NVGs, clearly needs investigation.

An accurate assessment of the effects of PLZT on aviator performance will require operational and task specific flight testing. Needed to be addressed are questions that consider mission profile, ambient light level, meteorological conditions, blast characteristics, separation distance, and aviator experience. From the standpoint of hardware, the effects of various forms of pyrotechnics need to be investigated in order to discern how PLZT's light sensors will respond under varying conditions of rapid illumination change. (Indeed, even the intermittent flicker caused by normal rotor blade rotation can, under certain lighting conditions, effectively trigger PLZT [McLean and Rash, 1985]). Also needed to be addressed are questions associated

with cockpit lighting. Current cockpit lighting configurations are not compatible with NVGs and must be operated at low level settings to minimize NVG degradation. A requirement to view instrument and indicator lights through PLZT will necessitate a higher light level setting and thereby reduce NVG performance. The aviator's ability to see his outside environment could thus be impaired and his aircraft rendered more vulnerable to enemy detection and localization.

#### Recommendations

The data from this study suggest PLZT in its open state can be used with NVGs without significantly impairing visual acuity. We are concerned greatly, however, both about flying with PLZT alone under low-light conditions and with PLZT-NVG compatibility. We cannot at this time offer an unqualified recommendation to incorporate PLZT into the HGU/56P. We recommend additional operational testing of PLZT material, especially with actual or prototype headgear.

## References

- Lindsey, R. L. 1988. Electro-optic performance of PLZT lenses. Brooks Air Force Base, TX: U.S. Air Force School of Aerospace Medicine. USAFSAM-TR-88-13.
- McLean, W. E., and Rash, C. E. 1985. U.S. Army aviation concept evaluation of the PLZT nuclear flashblindness protective goggles. Fort Rucker, AL: U.S. Army Aeromedical Research Laboratory. USAARL LR-85-11-2-7.
- Richey, E. O., Bower, J. L., and Allen, R. D. 1980. Evaluation of PLZT. Brooks Air Force Base, TX: U.S. Air Force School of Aerospace Medicine. Report SAM-TR-80-17.
- RCA Corporation. 1974. Electro-Optics Handbook. Lancaster, PA.
- Templin, P. S., and Thornton, E. 1978. Flyers flash blindness goggles (EEU-2/P). Eglin Air Force Base, FL: U.S. Air Force Tactical Air Warfare Center. TAC Project 77T-008T.
- Wetherill, G. B., and Levitt, H. 1965. Sequential estimation of points on a psychometric function. British journal of mathematical and statistical psychology. 18: 1-10.
- Wiley, R. W. 1987. Visual acuity and tinted lenses: Ambient luminance and target contrast. Fort Rucker, AL: U.S. Army Aeromedical Research Laboratory. Memorandum to Directorate of Combat Developments, U.S. Army Aviation Center, Fort Rucker, AL.
- Wiley, R. W., Glick, D. D., Bucha, C. T., and Park, C. K. 1976. Depth perception with the AN/PVS-5 night vision goggle. Fort Rucker, AL: U.S. Army Aeromedical Research Laboratory. USAARL Report 76-25.

**Appendix A**

**DCD request memorandum**

# DISPOSITION FORM

For use of this form, see AR 340-15; the proponent agency is TAGO.

REFERENCE OR OFFICE SYMBOL

ATZQ-CDM-C (70-1i)

SUBJECT

Evaluation of Visual Transmittance While Wearing Night Vision Goggles (NVG) and Nuclear Flashblindness Goggles

TO

Cdr, USAARL

FROM


Dir, DCD

DATE

CMT 1

Mr. Birringer/ncw/5272

1. The protection of the unaided eye against the effects of small tactical nuclear weapons (flashblindness) on the modern battlefield is an issue of concern for Army aviators. DCD is having difficulty defining the effects of reduced transmissivity of nuclear flashblindness goggles (PLZT) in terms of operational capability. This is particularly critical when aircraft are flying NOE at night and when pilots are wearing NVGs.
2. Request USAARL conduct an evaluation and analysis of the effects of visual transmittance through PLZT goggles worn in conjunction with NVGs. DCD will use this information to support or eliminate the operational capability currently required of the Aircrew Integrated Helmet (HGU-56/P). The HGU-56/P is currently in advanced development.
3. Also, request you provide a recommendation based on the analysis by 22 Nov 88.
4. DCD POC for this action is Mr. Birringer, extensions 5272/5071.

*for*   
THEODORE T. SENDAK  
Colonel, Aviation  
Director of Combat Developments

## Appendix B

Mean visual acuity with AN/PVS-5A night vision goggles with  
and without simulated flashblindness protective lenses  
under varying levels of brightness and contrast

	Minimum angle of resolution*		Snellen acuity**	
	No filter	Filter	No filter	Filter
<u>Twilight</u>				
High contrast	2.66	2.65	20/50-	20/50-
Moderate "	2.91	3.17	20/60	20/60
Low "	6.10	6.45	20/100-	20/150+
<u>Moonlight</u>				
High contrast	3.23	3.25	20/60-	20/60-
Moderate "	3.86	4.49	20/80	20/80-
Low "	9.74	9.28	20/200	20/200
<u>Starlight</u>				
High contrast	4.15	5.69	20/100	20/100-
Moderate "	6.63	7.11	20/150+	20/150
Low "	26.25	20.59	20/400-	20/400

\* Minutes of arc

\*\* Approximate Snellen equivalent based upon letter sizes  
actually presented to the subjects.

Appendix C

Manufacturers' list

Eastman Kodak Company  
Rochester, NY 14650

Photo Research  
3000 North Hollywood Way  
Burbank, CA 91505



Initial distribution

Commander  
U.S. Army Natick Research  
and Development Center  
ATTN: Documents Librarian  
Natick, MA 01760

Naval Submarine Medical  
Research Laboratory  
Medical Library, Naval Sub Base  
Box 900  
Groton, CT 05340

Commander/Director  
U.S. Army Combat Surveillance  
& Target Acquisition Lab  
ATTN: DELCS-D  
Fort Monmouth, NJ 07703-5304

Commander  
10th Medical Laboratory  
ATTN: Audiologist  
APO NEW YORK 09180

Commander  
Naval Air Development Center  
Biophysics Lab  
ATTN: G. Kydd  
Code 60B1  
Warminster, PA 18974

Naval Air Development Center  
Technical Information Division  
Technical Support Detachment  
Warminster, PA 18974

Commanding Officer  
Naval Medical Research  
and Development Command  
National Naval Medical Center  
Bethesda, MD 20014

Under Secretary of Defense  
for Research and Engineering  
ATTN: Military Assistant  
for Medical and Life Sciences  
Washington, DC 20301

Commander  
U.S. Army Research Institute  
of Environmental Medicine  
Natick, MA 01760

U.S. Army Avionics Research  
and Development Activity  
ATTN: SAVAA-P-TP  
Fort Monmouth, NJ 07703-5401

U.S. Army Research and Development  
Support Activity  
Fort Monmouth, NJ 07703

Chief, Benet Weapons Laboratory  
LCWSL, USA ARRADCOM  
ATTN: DRDAR-LCB-TL  
Watervliet Arsenal, NY 12189

Commander  
Man-Machine Integration System  
Code 602  
Naval Air Development Center  
Warminster, PA 18974

Commander  
Naval Air Development Center  
ATTN: Code 6021 (Mr. Brindle)  
Warminster, PA 18974

Commanding Officer  
Harry G. Armstrong Aerospace  
Medical Research Laboratory  
Wright-Patterson  
Air Force Base, OH 45433

Director  
Army Audiology and Speech Center  
Walter Reed Army Medical Center  
Washington, DC 20307-5001

Director  
Walter Reed Army Institute  
of Research  
Washington, DC 20307-5100

HQ DA (DASG-PSP-0)  
5109 Leesburg Pike  
Falls Church, VA 22041-3258

Naval Research  
Laboratory Library  
Code 1433  
Washington, DC 20375

Harry Diamond Laboratories  
ATTN: Technical Infor-  
mation Branch  
2800 Powder Mill Road  
Adelphi, MD 20783-1197

U.S. Army Materiel Systems  
Analysis Agency  
ATTN: Reports Processing  
Aberdeen Proving Ground  
MD 21005-5017

U.S. Army Ordnance Center  
and School Library  
Building 3071  
Aberdeen Proving Ground,  
MD 21005-5201

U.S. Army Environmental Hygiene  
Agency  
Building E2100  
Aberdeen Proving Ground,  
MD 21010

Technical Library  
Chemical Research  
and Development Center  
Aberdeen Proving Ground,  
MD 21010-5423

Commander  
U.S. Army Institute  
of Dental Research  
Walter Reed Army Medical Center  
Washington, DC 20307-5300

Naval Air Systems Command  
Technical Air Library 950D  
Rm 278, Jefferson Plaza II  
Department of the Navy  
Washington, DC 20361

Naval Research Laboratory Library  
Shock and Vibration Infor-  
mation Center, Code 5804  
Washington, DC 20375

Director  
U.S. Army Human Engineer-  
ing Laboratory  
ATTN: Technical Library  
Aberdeen Proving Ground,  
MD 21005-5001

Commander  
U.S. Army Test  
and Evaluation Command  
ATTN: AMSTE-AD-H  
Aberdeen Proving Ground,  
MD 21005-5055

Director  
U.S. Army Ballistic  
Research Laboratory  
ATTN: DRXBR-OD-ST Tech Reports  
Aberdeen Proving Ground,  
MD 21005-5066

Commander  
U.S. Army Medical Research  
Institute of Chemical Defense  
ATTN: SGRD-UV-AO  
Aberdeen Proving Ground,  
MD 21010-5425

Commander  
U.S. Army Medical Research  
and Development Command  
ATTN: SGRD-RMS (Ms. Madigan)  
Fort Detrick, Frederick,  
MD 21701

Commander  
U.S. Army Medical Research  
Institute of Infectious Diseases  
Fort Detrick, Frederick,  
MD 21701

Director, Biological  
Sciences Division  
Office of Naval Research  
600 North Quincy Street  
Arlington, VA 22217

Commander  
U.S. Army Materiel Command  
ATTN: AMCDE-XS  
5001 Eisenhower Avenue  
Alexandria, VA 22333

Commandant  
U.S. Army Aviation  
Logistics School  
ATTN: ATSQ-TDN  
Fort Eustis, VA 23604

U.S. Army Training  
and Doctrine Command  
ATTN: ATCD-ZX  
Fort Monroe, VA 23651

Structures Laboratory Library  
USARTL-AVSCOM  
NASA Langley Research Center  
Mail Stop 266  
Hampton, VA 23665

Naval Aerospace Medical  
Institute Library  
Bldg 1953, Code 102  
Pensacola, FL 32508

Command Surgeon  
U.S. Central Command  
MacDill Air Force Base  
FL 33608

Air University Library  
(AUL/LSE)  
Maxwell AFB, AL 36112

Commander  
U.S. Army Biomedical Research  
and Development Laboratory  
ATTN: SGRD-UBZ-I  
Fort Detrick, Frederick,  
MD 21701

Defense Technical  
Information Center  
Cameron Station  
Alexandria, VA 22313

U.S. Army Foreign Science  
and Technology Center  
ATTN: MTZ  
220 7th Street, NE  
Charlottesville, VA 22901-5396

Director,  
Applied Technology Laboratory  
USARTL-AVSCOM  
ATTN: Library, Building 401  
Fort Eustis, VA 23604

U.S. Army Training  
and Doctrine Command  
ATTN: Surgeon  
Fort Monroe, VA 23651-5000

Aviation Medicine Clinic  
TMC #22, SAAF  
Fort Bragg, NC 28305

U.S. Air Force Armament  
Development and Test Center  
Eglin Air Force Base, FL 32542

U.S. Army Missile Command  
Redstone Scientific  
Information Center  
ATTN: Documents Section  
Redstone Arsenal, AL 35898-5241

U.S. Army Research and Technology  
Laboratories (AVSCOM)  
Propulsion Laboratory MS 302-2  
NASA Lewis Research Center  
Cleveland, OH 44135

AFAMRL/HEX  
Wright-Patterson AFB, OH 45433

University of Michigan  
NASA Center of Excellence  
in Man-Systems Research  
ATTN: R. G. Snyder, Director  
Ann Arbor, MI 48109

John A. Dellinger,  
Southwest Research Institute  
P. O. Box 28510  
San Antonio, TX 78284

Product Manager  
Aviation Life Support Equipment  
ATTN: AMCPM-ALSE  
4300 Goodfellow Blvd.  
St. Louis, MO 63120-1798

Commander  
U.S. Army Aviation  
Systems Command  
ATTN: AMSAV-ED  
4300 Goodfellow Blvd  
St. Louis, MO 63120

Commanding Officer  
Naval Biodynamics Laboratory  
P.O. Box 24907  
New Orleans, LA 70189

U.S. Army Field Artillery School  
ATTN: Library  
Snow Hall, Room 14  
Fort Sill, OK 73503

Commander  
U.S. Army Health Services Command  
ATTN: HSOP-SO  
Fort Sam Houston, TX 78234-6000

U.S. Air Force Institute  
of Technology (AFIT/LDEE)  
Building 640, Area B  
Wright-Patterson AFB, OH 45433

Henry L. Taylor  
Director, Institute of Aviation  
University of Illinois-  
Willard Airport  
Savoy, IL 61874

COL Craig L. Urbauer, Chief  
Office of Army Surgeon General  
National Guard Bureau  
Washington, DC 50310-2500

Commander  
U.S. Army Aviation  
Systems Command  
ATTN: SGRD-UAX-AL (MAJ Lacy)  
4300 Goodfellow Blvd., Bldg 105  
St. Louis, MO 63120

U.S. Army Aviation Systems Command  
Library and Information  
Center Branch  
ATTN: AMSAV-DIL  
4300 Goodfellow Blvd  
St. Louis, MO 63120

Federal Aviation Administration  
Civil Aeromedical Institute  
CAMI Library AAC 64D1  
P.O. Box 25082  
Oklahoma City, OK 73125

Commander  
U.S. Army Academy  
of Health Sciences  
ATTN: Library  
Fort Sam Houston, TX 78234

Commander  
U.S. Army Institute  
of Surgical Research  
ATTN: SGRD-USM (Jan Duke)  
Fort Sam Houston, TX 78234-6200

Director of Professional Services  
AFMSC/GSP  
Brooks Air Force Base, TX 78235

U.S. Army Dugway Proving Ground  
Technical Library  
3Bldg 5330  
Dugway, UT 84022

U.S. Army Yuma Proving Ground  
Technical Library  
Yuma, AZ 85364

AFFTC Technical Library  
6520 TESTG/ENXL  
Edwards Air Force Base,  
CAL 93523-5000

Commander  
Code 3431  
Naval Weapons Center  
China Lake, CA 93555

Aeromechanics Laboratory  
U.S. Army Research  
and Technical Labs  
Ames Research Center,  
M/S 215-1  
Moffett Field, CA 94035

Sixth U.S. Army  
ATTN: SMA  
Presidio of San Francisco,  
CA 94129

Commander  
U.S. Army Aeromedical Center  
Fort Rucker, AL 36362

U.S. Air Force School  
of Aerospace Medicine  
Strughold Aeromedical Library  
Documents Section, USAFSAM/TSK-4  
Brooks Air Force Base, TX 78235

Dr. Diane Damos  
Department of Human Factors  
ISSM, USC  
Los Angeles, CA 90089-0021

U.S. Army White Sands  
Missile Range  
Technical Library Division  
White Sands Missile Range,  
NM 88002

U.S. Army Aviation Engineering  
Flight Activity  
ATTN: SAVTE-M (Tech Lib)  
Stop 217  
Edwards Air Force Base,  
CA 93523-5000

Ms. Sandra G. Hart  
Ames Research Center  
MS 239-5  
Moffett Field, CA 94035

Commander  
Letterman Army Institute  
of Research  
ATTN: Medical Research Library  
Presidio of San Francisco,  
CA 94129

Director  
Naval Biosciences Laboratory  
Naval Supply Center, Bldg 844  
Oakland, CA 94625

Commander  
U.S. Army Medical Materiel  
Development Activity  
Fort Detrick, Frederick,  
MD 21701-5009

Commander, U.S. Army  
Aviation Center  
Directorate  
of Combat Developments  
Bldg 507  
Fort Rucker, AL 36362

Chief  
Army Research Institute  
Field Unit  
Fort Rucker, AL 36362

Commander  
U.S. Army Safety Center  
Fort Rucker, AL 36362

U.S. Army Aircraft Development  
Test Activity  
ATTN: STEBG-MP-QA  
Cairns AAF  
Fort Rucker, AL 36362

Commander  
U.S. Army Medical Research  
and Development Command  
ATTN: SGRD-PLC (COL Sedge)  
Fort Detrick, Frederick  
MD 21701

Directorate  
of Training Development  
Bldg 502  
Fort Rucker, AL 36362

Chief  
Human Engineering Laboratory  
Field Unit  
Fort Rucker, AL 36362

Commander  
U.S. Army Aviation Center  
and Fort Rucker  
ATTN: ATZQ-T-ATL  
Fort Rucker, AL 36362

President  
U.S. Army Aviation Board  
Cairns AAF  
Fort Rucker, AL 36362